

HS1Plus

- 1.Portable, ultra-large capacity 3800mAh lithium polymer battery, Convenient for field use)
2. Support the whole machine charging and single battery charging
- 3.Support Type-C USB charging
- 4.Spectrum Dynamic Waterfall Display
- 5.Multiple Working Modes: Receive Mode, Transmit Mode, TUNE Mode, VFO Mode, SPLIT Mode
- 6.DSP Digital Signal Processing Noise Reduction
- 7.Automatic Notch Filter
- 8.Display board interface: Line output (J1), line input (J2), microphone /PTT (J3), speaker/mobile phone (J4)



HS1Plus

Feature:

- Frequency Range: 0.5MHz-30MHz
- Battery Capacity: 3800mAh Li-ion Battery
- Operating Mode: SSB(J3E), CW, AM, FM, FREE-DV
- TX Power: Maximum 15W
- Minimum Frequency Step: 1Hz
- Operating Voltage: 9-15V DC
- Antenna Impedance: 50Ω
- Frequency Stability: ±1.5PPM @ Power on 5 Minutes(Standard); ±0.5PPM if Optional TCXO Used
- Package Size: 243mm*198mm*87mm
- Packed Weight: 1706g (Include battery and bracket)

Technical parameters:

Frequency Range	RX: 0.5MHz-30MHz
	TX: 0.5MHz-30MHz
Output Power	Maximum 15W
Receiving Sensitivity	Better than -95dBm
Operating Mode	SSB(J3E), CW, AM, FM, FREE-DV
Dimensions	208mm*81.09mm*73.2mm
Operating Voltage Range	DC 9-15V
Maximum Current	3.5A
Battery Capacity	3800mAh Lithium-polymer Battery
	(DC11.1V)
Weight(Battery and Mounting Bracket Included)	919g
Transceiver comes with automatic key generator circuit, Can be connected to the use of automatic keys.	

Standard Accessories:

- 1 x User Manual
- 1 x Hand Microphon
- 1 x Mounting Bracket
- 1 x Adapter
- 1 x DC Power Cable
- 1 x 3800mAh Li-ion Battery
- 2 x Wrench
- 1 x Antenna Convertor
- 1 x HS1Plus HF SDR Transceiver



RETEVIS

kam@retevis.com www.reteis.com

SHENZHEN RETEVIS TECHNOLOGY CO.,LTD