

RB19&RB619

PMR446 16CH & FRS 22CH Channels

Feature:

- License-free
- Built-in battery, ultra-thin design, elegant appearance
- Switching channels by 1.7 inch matrix diode display
- Low power consumption design, long standby
- Type-C charging method
- Screen Display
- Scanning
- Monitoring
- VOX
- TOT
- Keyboard Lockout
- Power Display
- Busy Channel Lockout
- Power Saving Mode
- Low Battery Warning
- Voice Companding
- Scrambling Function
- Special Signaling
- 50 CTCSS/208 DCS



RB19&RB619

PMR446 16CH & FRS 22CH Channels

Specification:

EU: 446.00625-446.19375MHz Frequency range: US: 462.5500-467.7125MHz

Supply Power: DC3.7V

US: 22 CH Memory Channel: EU: 16CH

Antenna Configuration: Integrated antenna

Built-in 1650mAh li-ion battery Battery:

Work Mode: Co/Differ-frequency Simplex Communication

Ground Method: Cathode

-30°~+60° Working temperature range:

Transmitter

Ourput Power: US: ≤2W EU: ≤0.5W

Modulation Mode: FM(F3E) Max. Frequency Deviation: ≤5KHz

Sparious Radiation: ≤7.5µW Preemphasis Character: Per Octave 6dB

≤1000mA **Emission Current:**

Receiver

Sensitivity: <0.16µV(12dB SINAD)

≥300mW Audio power:

Audio Distortion: <5%

Itermodulation Interference Resistance: ≥60dB

≤300mA Receiving Current:

Standby Current: ≤20mA

Package includes:

1 x RB19&RB619 Walkie Talkie

1 x Power Adapter

1 x Type-C USB Cable

1 x User Manual





CE F© RoHS



Shenzhen Retevis Technology Co.,Ltd

Add: 7/F, 13-C, Zhonghaixin Science&Technology Park, No.12 Ganli 6th Road, Jihua Street, Longgang District, Shenzhen, China

Web: www.retevis.com E-mail: kam@retevis.com Facebook: facebook.com/retevis

