

RB628

16CH 0.5W PMR License-free Handheld Two Way Radio Walkie Talkie

Features:

- 1.Time out timer(TOT)
- 3. Busy Channel Lockout
- 5. Squelch level (0-9 grades)
- 7. Audio Compand option
- 9.CTCSS/DCS Encode/Decode
- 11.Scan function
- 13.2-pin Kenwood accessory port

- 2.VOX feature
- 4.Keyboard Lock (Auto/Manual)
- 6. Auto power saving function
- 8. Monitor function
- 10.Low power indication/alarm
- 12.Call ringtone (10 group)

Hot Spot:

- License-free PMR frequency
- 16 channels available

in in

- Designed with VOX hands free, supports
 PTT push to talk and voice activation talking;
- 1500mAh li-ion battery can last whole day use once be fully charged; low battery alert function helps you keep the walkie talkies always in power
- With 1.28 inch screen and Type-c charging cable (1 on 2)



RB628

16CH 0.5W PMR License-free Handheld Two Way Radio Walkie Talkie

Specification:

Frequency Range	446.00625~446.19375MHz (RX & TX)		
Memory Channel	16 CH		
Operation Voltage	DC3.7V ±10%		
Battery Capacity	1500mAh (li-ion)		
Step frequency	12.5KHz		
Working time (5:5:9)	12 Hours		
Antenna Impedance	50ohm		
Item Dimensions	105*52*21 mm		
Weight	body 82.7g battery 38.3g total 128g (include battery, belt clip)		

Electrical Properties:

GENERAL TRANSMI		TTER RECEIVER		IVER	
Frequency Rang	446.00625~ 446.19375Mz	Output power	0.5 W	RF sensitivity	≤0.25uV
Channel capacity	16 CH	Adjacent channel power	≥60dB	Opening sensitivity	≤0.20uV
Working Voltage	3.7 V	TX current	≤1.35A	Audio output	≥300mW
Antenna impedance	50Ω	Spurious radiation	≤7.5µW	Receive current	≤410 mA
Step frequency	12.5KHz	Modulation limited	≤2.5kH	Waiting current	≤20mA

Standard Accessories:

2* RB628 Two Way Radio 2* Li-ion Battery 2* Belt Clip 1*USB Charging Cable 1*User Manual



Shenzhen Retevis Technology Co.,Ltd. 7/F, 13-C, Zhonghaixin Science&Technology Park, No.12 Ganli 6th Road, Jihua Street, Longgang District, Shenzhen, China Web:www.retevis.com
E-mail:kam@retevis.com
Facebook:facebook.com/retevis

