

RETEVIS

RM01

Marine Transceiver

Features:

- IP67
- LCD
- Dual/Tri-watch Functions
- Battery Indicator
- Weather Channel Receive
- Favorite Channel Function

Description

- IPX7 Waterproof Construction(1 m depth of water for 30 minutes)
- Floating,Vibration Draining Function



RM01

Marine Transceiver

General

Frequency Range	TX:156.000-162.000MHz RX:156.000-163.275MHz
Type of Emission	FM(16K0F3E)
Frequency Stability	±10ppm
Frequency Interval	25kHz
NiMH Batteries	DC1.2V*5,850mAh (AAA)
Operating temperature	-20℃ ~ + 60℃
Dimension(HxWxD)	63*119*35mm
Weight (with battery)	136g
Waterproof Level	IP67

Receiver

Receiving sensitivity	≤0.2μV
Signal-to-Noise Ratio	≥40dB
Adjacent Channel Selectivity	≥65dB
Spurious Response Immunity	≥70dB
Intermodulation Rejection	≥68dB
Audio Output Power	≥0.6W

Transmitter

Output Power	3W/1W
Output Current	≤1.3A/0.8A
Max. Frequency Deviation	±5kHz
Spurious Emission	≤0.25μW
Adjacent Channel Power	≥65dB
Transmit Audio Distortion	≤5%

Package includes:

- 1 x Marine Transceiver
- 5 x 1.2V(AAA)Battery
- 1 x Antenna
- 1 x Belt clip
- 1 x Manual
- 1 x Adaptor
- 1 x Lanyard



Shenzhen Retevis Technology Co.,Ltd.

7/F, 13-C, Zhonghaixin Science&Technology Park, No.12 Ganli
6th Road, Jihua Street, Longgang District, Shenzhen, China

Web:www.retevis.com

E-mail:kam@retevis.com

Facebook:facebook.com/retevis



MADE IN CHINA