



VHF Marine Transceiver

General

Frequency Range: TX:156.025-157.425MHz, RX:156.050-163.275MHz

Type of Emission: FM(16K0G3E)/DSC(16K0G2B)

Frequency Stability: ±10ppm

Battery Pack: DC7.4V,1500mAh

Operating temperature: $-15^{\circ}\text{C} \sim +55^{\circ}\text{C}$

Dimension(HxWxD): 61*141*43mm

Weight: 315g (with battery, antenna and belt clip)

Waterproof Level: IPX7

Receiver

Receiving sensitivity: ≤0.22µV

Squelch Sensitivity: ≤0.22µV

HUM and Noise: ≥40dB

Adjacent Channel Selectivity: ≥70dB

Spurious Response Rejection Ratio: ≥70dB

Intermodulation Rejection Ratio: ≥68dB

Audio Output Power: ≥0.5W(10%)

Transmitter

RF power: 5W/1W

Maximum Frequency Deviation: ±5kHz

Spurious Emission: ≤0.25µW

Adjacent channel power: ≥70dB

Audio Harmonic Distortion: ≤10%

Current Drain: ≤1.5A(High Power),≤0.7A(Low Power),≤0.2A(Maximum Audio Output)

GPS Receiver

Apply to long-term tracking (when signal strength≥-130dBm, 5 satellites visible)

TIFF Cold Boot: <1 minute

TIFF Warm Boot: <10 seconds

Horizontal position Precision: < 10 meters

Package includes:

- 1 x Marine Transceiver
- 1 x Battery
- 1 x Antenna
- 1 x Car Charger
- 1 x Belt clip
- 1 x Manual
- 1 x Adaptor
- 1 x Desktop Charger
- 1 x Lanyard

CE F© RoHS



Shenzhen Retevis Technology Co.,Ltd.

Add: 7/F, 13-C, Zhonghaixin Science&Technology Park, No.12 Ganli 6th Road, Jihua Street, Longgang District, Shenzhen, China

Web: www.retevis.com
E-mail: kam@retevis.com
Facebook: facebook.com/retevis





