

RETCVIS

RT49P&RT649P

License-free FRS Handheld Two Way Radio

- CTCSS/DCS function
- Built-in Led torch
- Red light flash while falling into the water
- Float under water
- Power saving automatically
- Time-out-Time(TOT) function
- Scan function
- Squelch level
- Monitor
- Call tone
- Keypad locked
- Dual channels watch
- SOS function
- VOX
- Ending elimination
- End of launch tone
- Waterproof function
- NOAA function (US)



RT49P&RT649P

License-free PMR Handheld Two Way Radio

Specification :

| | |
|-----------------------|---------------------------------------------------------------------------------|
| Frequency Range | FRS:462.5500-467.7125 (NOAA161.6500-162.5250MHz) PMR: 446.00625-446.19375MHZ |
| Memory Channel | US: 22CH EU: 16CH |
| Operation Voltage | DC 3.6V / DC4.5V |
| Battery Capacity | 1200 mAh |
| Operating Temperature | -20°C-+60°C |
| Antenna Impedance | 50Ω |

Receiver

| | |
|--------------------------------|------------------|
| Receive Sensitivity | -125dBm |
| Adjacent Channel Selectivity | -125dBm |
| Inter Modulation and Rejection | ≥60dB |
| Rated Audio Power Output | ≥450mW (4.5V) |
| Rated Audio Distortion | ≤5% (60% volume) |
| Receive Current | ≤300mA |

Transmitter

| | |
|----------------------|------------------------------------|
| RF Output Power | US: 2.0W/0.5W (Hi/Low) EU: 0.5W |
| Spurious Emission | ≤-13dBm |
| Transmission current | ≤1.3A |

Package includes

- 2 x RT49P Two Way Radio
- 6 x NiMH Batteries
- 2 x Belt Clip
- 1 x USB charging Cable
- 1 x Drop-in charging tray
- 1 x Adapter
- 1 x User Manual
- 2 x RT649P Two Way Radio
- 6 x NiMH Batteries
- 2 x Belt Clip
- 1 x USB charging Cable
- 1 x Drop-in charging tray
- 1 x User Manual

CE FC RoHS



Shenzhen Retevis Technology Co.,Ltd

Add: 7/F, 13-C, Zhonghaixin Science&Technology Park, No.12 Ganli
6th Road, Jihua Street, Longgang District, Shenzhen, China

Web: www.retevis.com

E-mail: kam@retevis.com

Facebook: facebook.com/retevis



MADE IN CHINA