

RT56B&656B

Explosion-proof Handheld Transceiver

RETCV15

Feature:

- Scanning
- Local/Remote Emergency Alarm Function
- VOX Voice-operated Transmitted
- 1750Hz Tone Code Function
- CALL Function
- CTCSS/DCS/DTMF Encode and Decode
- FM Radio
- Chinese/English Voice Prompt
- Torch Light



RT56B&656B

Explosion-proof Handheld Transceiver

General

| | |
|-------------------------|---|
| Frequency for repeater: | US:FRS , EU:PMR446 |
| Channel: | US:22 , EU:16 |
| Modulation Type: | 8K5F3E |
| Frequency Step: | 5KHz/6.25KHz/10KHz/12.5KHz/25KHz/50KHz/100KHz |
| Power: | US:2W , EU:0.5W |
| Frequency stability: | ±2.5ppm |
| Working temperature: | -20°C ~ + 60°C |
| Working voltage: | DC7.4V |
| Battery Capacity: | 1800mAh (Li-ion) |
| Antenna Impedance: | 50Ω |
| Dimension(HxWxD): | 123*61*36.5mm |
| Weight: | 266g (With Battery, Antenna and Belt Clip) |

Receiver

| | |
|-------------------------------|-------------|
| Sensitivity(12dB SINAD): | ≤0.35μV |
| Adjacent channel selectivity: | ≥60dB |
| Intermodulation Rejection: | ≥60dB |
| Spurious Response Rejection: | ≥60dB |
| Blocking Characteristic: | ≥85dB |
| Audio Output: | >600mW @10% |

Transmitter

| | |
|--------------------------|-----------------|
| RF power: | US:2W , EU:0.5W |
| Max Frequency Deviation: | ±2.5kHz |
| Adjacent Channel Power: | ≥55dB |
| Spurious Radiation: | ≤-31dBm |
| Audio Distortion: | ≤5 % |

Package includes :

- Explosion-proof intercom X1
- Operating instruction X1
- Desktop Charger X1
- Explosion-proof Li-Pol Battery X1
- Belt Clip X1



CE FCC RoHS 

Shenzhen Retevis Technology Co.,Ltd.

Add: 7/F, 13-C, Zhonghaixin Science&Technology Park, No.12 Ganli
6th Road, Jihua Street, Longgang District, Shenzhen, China

Web: www.retevis.com

E-mail: kam@retevis.com

Facebook: facebook.com/retevis



MADE IN CHINA