

RT76P

GMRS licensed walkie-talkie

- FM Radio
- NOAA
- Monitor
- Scan
- Talk Around
- Singal Call
- Group(s) Call
- All call
- Remote Kill
- 1.4 inch lattice screen display
- Voice Compandor
- VOX Function
- Power On Screen Edit
- Dual-Band Frequency Standby
- Reverse Frequency
- Multiple Alarm Modes Selection
- Multiple Repeater Tone Modes Selection



RETEVIS

RT76P

GMRS licensed walkie-talkie

Specification:

Frequency Range	GMRS
Channel number	30
RF Power	<5W
Frequency Stability	±2.5ppm
Working Voltage	7.4V DC
Antenna Allocation	Pauperization antenna
Antenna Impedance	50Ω
Working mode	Same frequency single working or different frequency single working

Receiver

Sensitivity	≤0.2uV/≤0.25uV
Voice Output Power	≥500mW
Audio Distortion	≤5%
Obstruct	≥85dB
Intermodulation	≥65dB/≥60dB
Adjacent Channel Selection	≥65dB/≥60dB
Spurious Rejection	≥65dB
Receiving current	≤430mA

Transmitter

Adjacent Channel Power	≥65dB/≥62dB
Wide/Narrow	0.75kHz±0.1 kHz/0.4kHz±0.1kHz
Audio Distortion	≤5%
Modulation Sensitivity	8-12mV
Maximum Frequency Deviation	≤5KHz/≤2.5KHz
Spurious Power	≤7.5uW
Modulation Mode	16KΦF3E/ 11 KΦF3E
Transmit current	≤1.6A
Preemphasis Character	6dB/every time the frequency will increase

Package includes

- 1 x RT76P two way radio
- 1 x Battery
- 1 x Belt Clip
- 1 x Hand Strap
- 1 x User's Manual
- 1 x Desktop Charger

CE FC RoHS



Shenzhen Retevis Technology Co.,Ltd

Add: 7/F, 13-C, Zhonghaixin Science&Technology Park, No.12 Ganli
6th Road, Jihua Street, Longgang District, Shenzhen, China

Web: www.retevis.com

E-mail: kam@retevis.com

Facebook: facebook.com/retevis



MADE IN CHINA